OLD MAN EMU 4X4 SUSPENSION
A Division Of ARB Corporation Limited

Head Office: ARB Corporation Ltd
Postal Address: PO Box 105, Kilsyth 3137 Australia
Street Address: 42 - 44 Garden Street
Kilsyth, Victoria 3137 Australia
Tel: +61 3 9761 6622 • Fax: +61 3 9761 6807
www.arb.com.au
ABN 31 006 708 756

FK40 Bump Spacer

JK Jeep Wrangler

CONTENTS

Part Number	Qty	Description
3460007	2	Front Bump Spacer
3460008	2	Rear Bump Spacer
6151433	2	Bolt M10x1.5x75
6151434	4	Bolt M8 x1.25x70
6151066	2	M10 Flange Nut
6151032	4	M8 Nyloc Nut
4581044	4	M8 Flat Washer

INSTALLATION PROCEDURE









Front Spacer

1. Remove front coils from vehicle.
2. Place the Front Spacer centrally on the cup and mark the hole center. Drill a pilot hole using a ¼ or 6mm drill bit.
3. Drill open the pilot hole using a 7/16 or 10mm drill bit.
4. Place front spacer inside the coil spring and place on cup seat
5. Secure spacer using a M10 bolt and flange nut. Apply Loctite to the nut to ensure it is retained. Tighten using an allen key until the spacer is firmly secured.

Rear Spacer

1. Rear spacers are mounted on the rear axle, on top of two flats that are located next to the spring coils.
2. Secure spacer using 2 xM8 bolts, washers and Nyloc Nuts